



## ISO BEARING-SINGAPORE (PTE)LTD.



10 mm x 26 mm x 8 mm NTN 7000CG/GNP4  
angular contact ball bearings

Bearing No. 7000CG/GNP4

7000CG/GNP4 Bearing 2D drawings and 3D CAD  
models

Size	10x26x8 mm
Bore Diameter	10 mm
Outer Diameter	26 mm
Width	8 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
Angle ( ° )	15 °
Category	Miniature Precision Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.018
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7   ISO P4
Flanges	No
Material - Ball	Steel
Race Material	Steel
Raceway Style	1 Rib Outer Ring
Number of Bearings	1 (Single)
Contact Angle	15 Degree
Preload	Light
Cage Material	Nylon



## ISO BEARING-SINGAPORE (PTE)LTD.

Rolling Element	Ball Bearing
Mounting Arrangement	Universal
Flush Ground	Yes
Inch - Metric	Metric
Other Features	Single Row   Angular Contact
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Inner Race Width; 8MM Outer Race Width; Open Enclosure; ABEC 7   ISO P4 Precision; No Flange; Steel Ball Material; Steel Race Material; 1 (Single) Bearing
Category	Miniature Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	7000CG/GNP4
Weight / LBS	0.04
Bore	0.394 Inch   10 Millimeter
Inner Race Width	0.315 Inch   8 Millimeter
Outside Diameter	1.024 Inch   26 Millimeter
Flange Outside Diameter	0 Inch   0 Millimeter
Outer Race Width	0.315 Inch   8 Millimeter
bore diameter:	10 mm
radial static load capacity:	2200 N
outside diameter:	26 mm
operating temperature range:	-40 to 120 ° C
overall width:	8 mm
cage material:	Nylon



## ISO BEARING-SINGAPORE (PTE)LTD.

contact angle:	15 °
maximum rpm:	46000 rpm
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 4
closure type:	Open
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
weight:	0.018 kg
bearing material:	High Carbon Chrome Steel
manufacturer product page:	<a href="#">Click here</a>
radial dynamic load capacity:	4900 N