



## ISO BEARING-SINGAPORE (PTE)LTD.



6034ZZ Bearing 2D drawings and 3D CAD models

170,000 mm x 260,000 mm x 42,000 mm NTN  
6034ZZ deep groove ball bearings

Bearing No. 6034ZZ

Size	170x260x42 mm
Bore Diameter	170,000 mm
Outer Diameter	260,000 mm
Width	42,000 mm
d	170,000 mm
D	260,000 mm
B	42,000 mm
C	42,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	7.06
EAN	4547359338836
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	170MM Bore; 260MM



## ISO BEARING-SINGAPORE (PTE)LTD.

	Outside Diameter; 42MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6034ZZ
Weight / LBS	15.565
Outside Diameter	10.236 Inch   260 Millimeter
Outer Race Width	1.654 Inch   42 Millimeter
Bore	6.693 Inch   170 Millimeter
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	170 mm
precision rating:	ISO Class 0
outside diameter:	260 mm
finish/coating:	Uncoated
overall width:	42 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	42 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	42 mm
snap ring included:	Without Snap Ring



## ISO BEARING-SINGAPORE (PTE)LTD.

maximum rpm (grease):	2400 rpm
internal clearance:	CN
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	2800 RPM
dynamic load capacity:	168000 N
series:	60
static load capacity:	172000 N
manufacturer product page:	<a href="#">Click here</a>